


Cat6 - FTP - STUG - LSZH

Categorie	F/UTP CAT6-4P-LSZH																																																																		
Referentie	ISO/IEC 11801 TIA-568-C.2																																																																		
CPR Classificatie	Eca																																																																		
Kern	Stug - 100% koper																																																																		
Afscherming	FTP	Technische prestaties (100m):																																																																	
AWG	23	<table><tr><th>Frequentie (Mhz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>Phase DELAY ≤ns</th></tr><tr><td>1</td><td>20.0</td><td>-</td><td>74.3</td><td>570.00</td></tr><tr><td>4.0</td><td>23.0</td><td>3.78</td><td>65.3</td><td>552.00</td></tr><tr><td>8.0</td><td>24.5</td><td>5.32</td><td>60.8</td><td>546.73</td></tr><tr><td>10.0</td><td>25.0</td><td>5.95</td><td>59.3</td><td>545.38</td></tr><tr><td>16.0</td><td>25.0</td><td>7.55</td><td>56.2</td><td>543.00</td></tr><tr><td>20.0</td><td>25.0</td><td>8.47</td><td>54.8</td><td>542.05</td></tr><tr><td>25.0</td><td>24.3</td><td>9.51</td><td>53.3</td><td>541.20</td></tr><tr><td>31.25</td><td>23.6</td><td>10.67</td><td>51.9</td><td>540.44</td></tr><tr><td>62.5</td><td>21.5</td><td>15.38</td><td>47.7</td><td>538.55</td></tr><tr><td>100</td><td>20.1</td><td>19.80</td><td>44.3</td><td>537.60</td></tr><tr><td>200</td><td>18.0</td><td>28.98</td><td>39.8</td><td>536.54</td></tr><tr><td>250</td><td>17.3</td><td>32.85</td><td>38.3</td><td>536.27</td></tr></table>	Frequentie (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase DELAY ≤ns	1	20.0	-	74.3	570.00	4.0	23.0	3.78	65.3	552.00	8.0	24.5	5.32	60.8	546.73	10.0	25.0	5.95	59.3	545.38	16.0	25.0	7.55	56.2	543.00	20.0	25.0	8.47	54.8	542.05	25.0	24.3	9.51	53.3	541.20	31.25	23.6	10.67	51.9	540.44	62.5	21.5	15.38	47.7	538.55	100	20.1	19.80	44.3	537.60	200	18.0	28.98	39.8	536.54	250	17.3	32.85	38.3	536.27
Frequentie (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase DELAY ≤ns																																																															
1	20.0	-	74.3	570.00																																																															
4.0	23.0	3.78	65.3	552.00																																																															
8.0	24.5	5.32	60.8	546.73																																																															
10.0	25.0	5.95	59.3	545.38																																																															
16.0	25.0	7.55	56.2	543.00																																																															
20.0	25.0	8.47	54.8	542.05																																																															
25.0	24.3	9.51	53.3	541.20																																																															
31.25	23.6	10.67	51.9	540.44																																																															
62.5	21.5	15.38	47.7	538.55																																																															
100	20.1	19.80	44.3	537.60																																																															
200	18.0	28.98	39.8	536.54																																																															
250	17.3	32.85	38.3	536.27																																																															
Diameter kabel	7,4 mm																																																																		
Lengte	350m																																																																		
Bandbreedte	250.0 MHz																																																																		
Buigradius	8x Diameter kabel																																																																		
Maximale trekkracht (Mpa)	≥ 12.5																																																																		
Materiaal buitenmantel	LSZH	<table><tr><th>Frequentie (Mhz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≤dB</th><th>PSELFEXT ≥dB</th></tr><tr><td>1</td><td>72.3</td><td>67.8</td><td>64.8</td></tr><tr><td>4.0</td><td>63.3</td><td>55.8</td><td>52.8</td></tr><tr><td>8.0</td><td>58.8</td><td>49.7</td><td>46.7</td></tr><tr><td>10.0</td><td>57.3</td><td>47.8</td><td>44.8</td></tr><tr><td>16.0</td><td>54.2</td><td>43.7</td><td>40.7</td></tr><tr><td>20.0</td><td>52.8</td><td>41.8</td><td>38.8</td></tr><tr><td>25.0</td><td>51.3</td><td>39.8</td><td>36.8</td></tr><tr><td>31.25</td><td>49.9</td><td>37.9</td><td>34.9</td></tr><tr><td>62.5</td><td>45.4</td><td>31.9</td><td>28.9</td></tr><tr><td>100</td><td>42.3</td><td>27.8</td><td>24.8</td></tr><tr><td>200</td><td>37.8</td><td>21.8</td><td>18.8</td></tr><tr><td>250</td><td>36.3</td><td>19.8</td><td>16.8</td></tr></table>	Frequentie (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB	1	72.3	67.8	64.8	4.0	63.3	55.8	52.8	8.0	58.8	49.7	46.7	10.0	57.3	47.8	44.8	16.0	54.2	43.7	40.7	20.0	52.8	41.8	38.8	25.0	51.3	39.8	36.8	31.25	49.9	37.9	34.9	62.5	45.4	31.9	28.9	100	42.3	27.8	24.8	200	37.8	21.8	18.8	250	36.3	19.8	16.8													
Frequentie (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB																																																																
1	72.3	67.8	64.8																																																																
4.0	63.3	55.8	52.8																																																																
8.0	58.8	49.7	46.7																																																																
10.0	57.3	47.8	44.8																																																																
16.0	54.2	43.7	40.7																																																																
20.0	52.8	41.8	38.8																																																																
25.0	51.3	39.8	36.8																																																																
31.25	49.9	37.9	34.9																																																																
62.5	45.4	31.9	28.9																																																																
100	42.3	27.8	24.8																																																																
200	37.8	21.8	18.8																																																																
250	36.3	19.8	16.8																																																																
Kleur buitenmantel	Blauw																																																																		
Aderkleuren	1 - Wit-Blauw/ Blauw																																																																		
	2 - Wit-Oranje/ Oranje																																																																		
	3 - Wit-Groen/ Groen																																																																		
	4 - Wit-Bruin/ Bruin																																																																		
Rip-cord	Aanwezig																																																																		
Verpakking	Haspel																																																																		